U.S. Application No. 09/766,577

Docket No. 0905-0254P

August 10, 2004 Art Unit: 2612

Page 3 of 10

AMENDMENT TO THE CLAIMS

The listing of the claims will replace all prior listings of claims in the application.

Listing of Claims

1. (Original) An image sensing apparatus comprising:

an image sensing device for sensing the image of a subject and outputting image

data representing the image of the subject;

a display control unit for controlling a display unit in such a manner that the image of

the subject represented by the image data output from said image sensing device will be

displayed on a display screen;

a designating unit for designating an electronic zoom area in the image of the

subject displayed on the display screen;

a light-emission control unit for controlling a strobe light-emission device in such a

manner that a part of the subject that corresponds to an image within the electronic zoom

area is illuminated with strobe light; and

a recording control unit for recording, on a recording medium, image data output

from said image sensing device and data indicating position of the electronic zoom area or

image data representing the image within the electronic zoom area.

2. (Original) An image sensing method comprising the steps of:

U.S. Application No. 09/766,577

Docket No. 0905-0254P

August 10, 2004

Art Unit: 2612 Page 4 of 10

sensing the image of a subject and outputting image data representing the image

of the subject;

displaying the image of the subject represented by the obtained image data on a

display screen of a display unit;

illuminating, with strobe light, a part of the subject that corresponds to an image

within an electronic zoom area designated in the image of the subject displayed on the

display screen; and

recording, on a recording medium, image data obtained by image sensing and

data indicating position of the electronic zoom area or image data representing the

image within the electronic zoom area.

3. (New) The image sensing apparatus in claim 1, wherein an optic axis of the

strobe light-emission unit coincides with a center point of the electronic zoom area.

4. (New) The image sensing apparatus in claim 1, wherein the image comprises

a marking that is displayed at a center point of the electronic zoom area.